

Instruction

DNAKE S617 provides an integrated security solution. It enables user to open the door by facial recognition with liveness detection, IC & ID card and PIN Code. It also makes an easy video call with indoor monitor and mobile APP, to achieve an convenient and secure life.

Key Features

- 8-inch IPS LCD capacitive touch screen
- 3 output relays for door locks
- 120° wide-angle 2MP HD camera with automatic lighting
- Support WDR technology to lighten the dark areas and darken the overexposed parts of the image
- Support 20,000 users, 20,000 faces, and 60,000 cards
- Tamper alarm

Physical

- | | |
|---|---|
| • System: Android | • Door Entry: Face, IC (13.56MHz) & ID (125kHz) card, PIN code, Bluetooth |
| • RAM: 2 GB | • Reset Button: 1 |
| • ROM: 8 GB | • RS485 Port: 1 |
| • Front Panel: Aluminum | • Relay Out: 3 |
| • Power Supply: PoE+ (802.3at) or DC 12V/3A | • Input: 4 |
| • Standby Power: 8 W | • IP / IK Rating: IP65 / IK08 |
| • Rated Power: 16 W | • Installation: Surface Mounting |
| • Camera: 2MP, CMOS, WDR | • Surface Mounting DIM: 140 x 300 x 41.8 mm |
| • IR Sensor: Support | • Working Temperature: -40°C to +55°C |
| • Wiegand Port: Support | • Storage Temperature: -40°C to +70°C |
| • Ethernet Port: 1 x RJ45, 10/100 Mbps adaptive | • Working Humidity: 10% to 90% (non-condensing) |

DNAKE S617 (Surface Mounting)



Datasheet

Display

- Display: 8-inch IPS LCD
- Resolution: 1280 x 800

Networking

- Protocol: ONVIF, SIP, UDP, TCP, RTP, RTSP, NTP, DNS, HTTP, DHCP, IPV4, ARP, ICMP

Audio

- Audio Codec: G.711
- Echo Cancellation
- DTMF: RFC2833
- Microphone: Built-in microphone
- Speaker: 8Ω / 1W

Video

- Video Codec: H.264
- Video Resolution: up to 1920 x 1080
- Viewing Angle: 120° (H) / 75° (V) / 131° (D)
- Max. Image Transfer Rate: 1080p – 25fps
- Light Compensation: LED white light



Instruction

DNAKE S617 provides an integrated security solution. It enables user to open the door by facial recognition with liveness detection, IC & ID card and PIN Code. It also makes an easy video call with indoor monitor and mobile APP, to achieve an convenient and secure life.

Key Features

- 8-inch IPS LCD capacitive touch screen
- 3 output relays for door locks
- 120° wide-angle 2MP HD camera with automatic lighting
- Support WDR technology to lighten the dark areas and darken the overexposed parts of the image
- Support 20,000 users, 20,000 faces, and 60,000 cards
- Tamper alarm

Physical

- | | |
|---|---|
| • System: Android | • Door Entry: Face, IC (13.56MHz) & ID (125kHz) card, PIN code, Bluetooth |
| • RAM: 2 GB | • Reset Button: 1 |
| • ROM: 8 GB | • RS485 Port: 1 |
| • Front Panel: Aluminum | • Relay Out: 3 |
| • Power Supply: PoE+ (802.3at) or DC 12V/3A | • Input: 4 |
| • Standby Power: 8 W | • IP / IK Rating: IP65 / IK08 |
| • Rated Power: 16 W | • Installation: Flush Mounting |
| • Camera: 2MP, CMOS, WDR | • Surface Mounting DIM: 140 x 300 x 60.3 mm |
| • IR Sensor: Support | • Working Temperature: -40°C to +55°C |
| • Wiegand Port: Support | • Storage Temperature: -40°C to +70°C |
| • Ethernet Port: 1 x RJ45, 10/100 Mbps adaptive | • Working Humidity: 10% to 90% (non-condensing) |

DNAKE S617 (Flush Mounting)



Datasheet

Display

- Display: 8-inch IPS LCD
- Resolution: 1280 x 800

Networking

- Protocol: ONVIF, SIP, UDP, TCP, RTP, RTSP, NTP, DNS, HTTP, DHCP, IPV4, ARP, ICMP

Audio

- Audio Codec: G.711
- Echo Cancellation
- DTMF: RFC2833
- Microphone: Built-in microphone
- Speaker: 8Ω / 1W

Video

- Video Codec: H.264
- Video Resolution: up to 1920 x 1080
- Viewing Angle: 120° (H) / 75° (V) / 131° (D)
- Max. Image Transfer Rate: 1080p – 25fps
- Light Compensation: LED white light

