

## DNAKE UM5-F19

### Instruction

The DNAKE Security Relay I/O Module UM5-F19 enables DNAKE Door Station to open two doors, for example, main door and garage door. It also enables elevator to reach the first floor automatically for the resident or visitor after the door is open.



### Key Features

- Two relays
- Two exit buttons
- Unlock time setting

### Physical

- Material: Plastic
- Power Supply: DC12V $\pm$ 10%
- Unlock Current: Maximum 3.5 A
- Standby Power: 1 W
- Rated Power: 1W
- Dimension: 114.5 x 57.5 x 34 mm
- RS485: 1
- Exit Button: 2
- Fire Linkage: Yes
- Unlock Time Setting: Yes
- Working Temperature: -40°C $\sim$ +55°C
- Storage Temperature: -40°C $\sim$ +70°C
- Working Humidity: 10% to 90% (non-condensing)

### Package Features

- Package Content:
  - DNAKE UM5-F19  
(Power adapter not included)
  - Screwing Kit
  - Quick Start Guide
- Qty/CTN: 81 pcs
- N.W/PCS: 0.12 kg
- G.W/CTN: 12.60 kg
- Giftbox Size: 120 x 65 x 45 mm
- Carton Size: 375 x 440 x 200 mm

